# SkyBlend® PARTICLEBOARD

#### DILLARD, OR • MISSOULA, MT • TAYLORSVILLE, MS

TECHNICAL DATA	DILLARD	MISSOULA	TAYLORSVILLE
Widths	4 & 5 ft	4 & 5 ft	4 & 5 ft
Lengths	up to 12 ft	up to 12 ft	up to 12 ft
Thicknesses	3/8 – 1-1/8 in	1/2 – 1-1/8 in	1/2 – 1-1/8 in
Density	47 lbs/ft <sup>3</sup>	46 lbs/ft <sup>3</sup>	50 lbs/ft <sup>3</sup>
Internal Bond	80 psi	80 psi	80 psi
Modulus of Rupture/MOR	2,100 psi	1,900 psi	1,900 psi
Modulus of Elasticity/MOE	400,000 psi	400,000 psi	350,000 psi
Screw Holding - Face	250 lbs	250 lbs	250 lbs
Screw Holding – Edge	200 lbs	180 lbs	200 lbs
Thickness Swell	≤ 5.5%	≤ 8.0%	≤ 5.5%
Linear Expansion	≤ 0.40%		
Flame Spread Rating	Class C (3)		
Dimensional Tolerances:			
Length/Width	±0.080 in		
Squareness	±0.036 in/ft		
Thickness – panel average from specified	±0.008 in		
Thickness – variance from panel average	±0.004 in		

PARTICLEBOARD

Composite wood particleboard panel produced with ultra low emitting formaldehyde (ULEF) resin system.

## COMMON APPLICATIONS

- Cabinets
- Furniture
- Shelving
- Countertops
- Laminating
- Door core
- Green building projects seeking low-emitting materials

Values represent averages for 3/4" panels. Mechanical properties are tested in accordance with ASTM D1037.

Customer-specified grades are available by request and subject to minimum order quantities.

SkyBlend® is also available from our Dillard, OR location in door core grades and sizes.



3660 Gateway St, Springfield, OR 97477 800.245.1115 | **roseburg.com** 





## DILLARD, OR • TAYLORSVILLE, MS • MISSOULA, MT

STANDARDS & CERTIFICATIONS			
Roseburg SkyBlend Particleboard is tested and certified to meet or exceed the following standards and certifications.			
ANSI A208.1 – American National Standard – Particleboard for Interior Applications			
$\checkmark$	Meets or exceeds general requirements of ANSI A208.1		
$\checkmark$	Meets Grade MR10 moisture resistance (Dillard, OR and Taylorsville, MS only)		
Formaldehyde Emissions Regulations – Third party certified (TPC-1) to meet the requirements of:			
$\checkmark$	EPA Formaldehyde Emission Regulation, TSCA Title VI*		
$\checkmark$	Ultra Low Emitting Formaldehyde (ULEF) Exempt - State of California Executive Orders: N-19-155 (Dillard, OR) N-18-319 (Missoula, MT) N-19-149 (Taylorsville, MS)		
Recycled Content			
$\checkmark$	90% pre-consumer recycled content in accordance with ISO 14021 requirements*		
Forest Stewardship Council®			
$\checkmark$	Scientific Certification Systems Certified (SCS-COC/CW-00300) – FSC-C017580 FSC® Mix and FSC® Controlled Wood - AVAILABLE OPTION*		
Environmental Product Declaration			
$\checkmark$	Type III Product Specific EPD Certified by UL Environment*		
Eco-Certified Composite Grademark Program			
$\checkmark$	CPA ECC Sustainability Standard*		
*Certificates and documentation available at Roseburg.com			

### **GREEN BUILDING SUPPORT:**

For LEED® and other green building support documentation, visit roseburg.com/product/skyblend-particleboard



3660 Gateway St, Springfield, OR 97477 800.245.1115 | **roseburg.com** 

